NSN 5930-01-199-7191

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-199-7191

Here the standard terms at 18 of the
Hazardous Locations/environmental Protection:
Oiltight and watertight
Overall Length:
1.540 inches
Overall Height:
4.220 inches
Overall Width:
2.460 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Height:
0.625 inches
Housing Height:
1.780 inches
Housing Length:
4.220 inches
Housing Width:
1.540 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
3.0 inch-ounces
Contact Load Current Rating At Maximum Rated Voltage:
50.000 milliamperes resistive dc and 6.000 amperes resistive ac
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-199-7191

Sensitive Switch - Page 2 of 2



Fiig:

A053a0