

View Online at <https://aerobasegroup.com/nsn/5930-01-199-8889>

Hazardous Locations/environmental Protection:

Shock proof and vibration proof

Overall Length:

4.637 inches

Overall Height:

3.688 inches

Overall Width:

4.375 inches

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.562 inches single actuator

Unthreaded Mounting Hole Diameter:

0.312 inches single mounting facility

Distance Between Mounting Facility Centers:

3.812 inches single mounting facility

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round w/through hole single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Special Features:

Two spacers before section one and one spacer after section two

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15291/7 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0