## NSN 5930-01-200-3263

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

1.000 inches

Overall Height:
1.183 inches

Overall Width:
0.755 inches

Body Width:

Corrosion resistant



View Online at https://aerobasegroup.com/nsn/5930-01-200-3263

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

U.	755 inches
С	ase Material:
Р	lastic
U	nthreaded Mounting Hole Diameter:
0.	138 inches
S	witch Actuator Quantity:
2	
Α	ctuator Style:
R	ound
Α	ctuator Diameter:
0.	070 inches
Α	ctuator Height:
0.	028 inches
Α	ctuator Adapter Style:
R	oller arm
M	aximum Voltage Rating In Volts:
28	3.0 dc
In	closure Type:
Н	ermetically sealed
M	ounting Method:
U	nthreaded hole
N	onpile-up Contact Arrangement:
2	pole, double throw, one position momentary single switch unit
S	witch Release Force:
4.	0 ounces
S	witch Actuating Force:
48	3.0 ounces
Α	ctuator Movement:
В	etween 0.040 pretravel inches and 0.125 overtravel inches and 0.040 differential inches
С	ontact Load Current Rating At Maximum Rated Voltage:
_	000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc

## NSN 5930-01-200-3263

Sensitive Switch - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

6 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0