NSN 5930-01-200-3263

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-200-3263

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.183 inches

Overall Width:

0.755 inches

Body Width:

0.755 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.138 inches

Switch Actuator Quantity:

2

Actuator Style:

Round

Actuator Diameter:

0.070 inches

Actuator Height:

0.028 inches

Actuator Adapter Style:

Roller arm

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc

NSN 5930-01-200-3263

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0