NSN 5930-01-200-4032

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-200-4032

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Fungus resistant and moisture proof |
| Body Length: |
| Between 1.025 inches and 1.034 inches |
| Body Width: |
| Between 0.775 inches and 0.784 inches |
| Body Height: |
| 2.440 inches |
| Actuator Length: |
| 0.891 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.070 inches |
| Actuator Width: |
| 0.668 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| Advance) single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, two positions momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 |
| amperes inductive ac and 750.000 milliamperes lamp ac |
| Terminal Type And Quantity: |
| 9 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-01-200-4032

Push Switch - Page 2 of 2



Fiig:

A053a0