

View Online at <https://aerobasegroup.com/nsn/5930-01-200-7448>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Splashproof

Bushing Length:

0.500 inches

Body Length:

1.650 inches

Body Width:

0.670 inches

Actuator Style:

Round

Actuator Diameter:

0.042 inches

Actuator Height:

1.800 inches

Actuator Position-action Relationship:

Center position maintained and left position maintained and right position maintained

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Lkk

Mounting Surface To Terminal End Distance:

1.000 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing w/panel seal

Features Provided:

Mounting hardware

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Contact Load Current Rating At Maximum Rated Voltage:

2.500 amperes resistive ac

Special Features:

Actuator is pulled out to change positions

Precious Material And Location:

Contacts plated gold

Test Data Document:

98230-0n346936 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0