

View Online at <https://aerobasegroup.com/nsn/5930-01-200-7879>

Thread Class:

2b single threaded hole

Overall Length:

5.660 inches

Overall Height:

4.350 inches

Body Height:

3.400 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

4.980 inches

End Application:

Centrifugal pump 60

Pressure Switch Type:

Differential

Mounting Method:

Threaded hole and unthreaded hole

Features Provided:

Electrical access port and manual reset button

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.250 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

20.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+9.82/+100.00 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point pointer with scale

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

Special Features:

High pressure cut-out (100 to 425 psig adjustable)

Media For Which Designed:

Liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unf single threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0