

View Online at <https://aerobasegroup.com/nsn/5930-01-200-7881>

Hazardous Locations/environmental Protection:

Fungus resistant and humidity resistant and vibration resistant

Overall Length:

2.680 inches

Overall Height:

1.380 inches

Overall Width:

2.070 inches

Mounting Slot Width:

0.218 inches

Body Length:

1.740 inches

Unthreaded Mounting Hole Diameter:

0.218 inches

Distance Between Mounting Facility Centers:

2.220 inches

Capillary Tube Length:

24.00 inches

Temperature Sensing Element Type:

Capillary tube

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and slot and unthreaded hole

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

27.00 actuation point degrees fahrenheit and 35.50 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0