NSN 5930-01-200-7881

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-200-7881

Hazardous Locations/environmental Protection:

Fungus resistant and humidity resistant and vibration resistant

Overall Length:

2.680 inches

Overall Height:

1.380 inches

Overall Width:

2.070 inches

Mounting Slot Width:

0.218 inches

Body Length:

1.740 inches

Unthreaded Mounting Hole Diameter:

0.218 inches

Distance Between Mounting Facility Centers:

2.220 inches

Capillary Tube Length:

24.00 inches

Tempurature Sensing Element Type:

Capillary tube

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and slot and unthreaded hole

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

27.00 actuation point degrees fahrenheit and 35.50 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-200-7881

Thermostatic Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0