NSN 5930-01-200-7882

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-200-7882 **Thread Class:** 3a single threaded bushing **Thread Length:** 12.31 millimeters single threaded bushing **Overall Length:** 95.8 millimeters **End Application:** 3805-01-153-1854 scraper, earth Width Across Flats: 25.4 millimeters **Operating Tempurature Rating:** Between -40.0 degrees fahrenheit and 121.0 degrees fahrenheit **Mounting Method:** Threaded bushing **Contact Action Stimulus:** Increase **Thread Size:** 0.750 inches single threaded bushing **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Tab w/screw **Contact Load Current Rating:** 40.0 milliamperes resistive load second voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 11.00 actuation point liters per minute and 4.90 deactuation point liters per minute **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage **Special Features:** 11.9 mm diameter paddle Media For Which Designed: Liquid **Style Designator:** Cylindrical **Thread Series Designator:** Unf single threaded bushing Shelf Life: N/a

--

Unit Of Measure:

NSN 5930-01-200-7882

Flow Switch - Page 2 of 2



Demi			

No

Fiig:

A048b0