

View Online at <https://aerobasegroup.com/nsn/5930-01-200-8564>

**Hazardous Locations/environmental Protection:**

Fungus proof and salt spray proof

**Overall Height:**

5.750 inches

**Overall Width:**

2.370 inches

**Body Height:**

3.000 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.720 inches

**Longest Vertical Distance Between Mounting Centers:**

2.720 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Proof Pressure:**

3000.00 pounds per square inch

**Thread Size:**

0.500 inches single threaded hole

**Mounting Facility Pattern:**

Two position diagonal

**Contact Load Current Rating:**

10.0 amperes inductive load third voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+5.00/+20.00 actuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Stimulus Rating:**

20.00 actuation point pounds per square inch and 200.00 actuation point pounds per square inch and 20.00 deactuation point pounds per square inch and 180.00 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

480.0 ac at sea level third voltage

**Pressure Connector Type:**

Swivel nut, compression, threaded internal single connection

**Frequency In Hertz:**

60.0 third voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0