

View Online at <https://aerobasegroup.com/nsn/5930-01-200-8564>

Hazardous Locations/environmental Protection:

Fungus proof and salt spray proof

Overall Height:

5.750 inches

Overall Width:

2.370 inches

Body Height:

3.000 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Proof Pressure:

3000.00 pounds per square inch

Thread Size:

0.500 inches single threaded hole

Mounting Facility Pattern:

Two position diagonal

Contact Load Current Rating:

10.0 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+5.00/+20.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Stimulus Rating:

20.00 actuation point pounds per square inch and 200.00 actuation point pounds per square inch and 20.00 deactuation point pounds per square inch and 180.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level third voltage

Pressure Connector Type:

Swivel nut, compression, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0