

View Online at <https://aerobasegroup.com/nsn/5930-01-201-1473>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Height:**

5.281 inches

**Overall Width:**

2.593 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Thready Qty Per Inch (tpi):**

18 first pressure connection

**Proof Pressure:**

2000.00 pounds per square inch gage

**Thread Size:**

0.500 inches second threaded hole

**Mounting Facility Pattern:**

Two position in-line

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+1.00/+30.00 actuation point pounds per square inch gage and +0.50/+28.50 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

0.10 differential point pounds per square inch gage and 1.50 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

6.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Special Features:**

Tamper proof external adjustment, contains viton diaphragm

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt second threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0