

View Online at <https://aerobasegroup.com/nsn/5930-01-201-1473>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

5.281 inches

Overall Width:

2.593 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 first pressure connection

Proof Pressure:

2000.00 pounds per square inch gage

Thread Size:

0.500 inches second threaded hole

Mounting Facility Pattern:

Two position in-line

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+1.00/+30.00 actuation point pounds per square inch gage and +0.50/+28.50 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

0.10 differential point pounds per square inch gage and 1.50 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

6.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

Tamper proof external adjustment, contains viton diaphragm

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt second threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0