

View Online at <https://aerobasegroup.com/nsn/5930-01-201-1950>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant and salt spray resistant and shock resistant and vibration resistant

Body Length:

0.750 inches

Body Width:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Width:

0.620 inches

Actuator Color:

Green single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

115 vac/28 vdc single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

Special Features:

Split display

Precious Material And Location:

Contacts silver and terminals gold

Unable To Decode:

Unable to decode and unable to decode

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 tab, solder lug and 3 turret

Specification Data:

81349-mil-s-22885/90 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0