

View Online at <https://aerobasegroup.com/nsn/5930-01-201-1950>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Fungus resistant and moisture resistant and salt spray resistant and shock resistant and vibration resistant

**Body Length:**

0.750 inches

**Body Width:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.620 inches

**Actuator Color:**

Green single actuator

**Illuminated Actuator Color:**

Green single actuator

**Actuator Inscription:**

115 vac/28 vdc single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc

**Special Features:**

Split display

**Precious Material And Location:**

Contacts silver and terminals gold

**Unable To Decode:**

Unable to decode and unable to decode

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 tab, solder lug and 3 turret

**Specification Data:**

81349-mil-s-22885/90 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0