NSN 5930-01-201-1952

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-201-1952

Body Style:						
Panel mount						
Hazardous Locations/environmental Protection:						
Fungus resistant and moisture resistant and salt spray resistant and shock resistant and vibration resistant						
Body Length:						
0.750 inches						
Body Width:						
0.750 inches						
Case Material:						
Metal						
Actuator Length:						
0.620 inches						
Actuator Style:						
Rectangular						
Actuator Width:						
0.620 inches						
Actuator Color:						
Green single actuator						
Illuminated Actuator Color:						
Green single actuator						
Actuator Inscription:						
Remote local single actuator						
Maximum Voltage Rating In Volts:						
28.0 dc						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Panel						
Nonpile-up Contact Arrangement:						
1 pole, double throw, one position momentary single switch unit						
Contact Load Current Rating At Maximum Rated Voltage:						
7.000 amperes resistive dc and 4.000 amperes inductive dc						
Special Features:						
Split display						
Precious Material And Location:						
Contacts silver and terminals gold						
Unable To Decode:						
Unable to decode and unable to decode						
Terminal Type And Quantity:						
5 tab, solder lug and 3 turret						
Shelf Life:						
N/a						

NSN 5930-01-201-1952

Push Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A053a0