## NSN 5930-01-201-1952

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-201-1952

## Body Style:

Panel mount

#### Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant and salt spray resistant and shock resistant and vibration resistant

#### Body Length:

0.750 inches

#### Body Width:

0.750 inches

#### **Case Material:**

Metal

#### Actuator Length:

0.620 inches

#### Actuator Style:

Rectangular

#### Actuator Width:

0.620 inches

#### Actuator Color:

Green single actuator

## Illuminated Actuator Color:

Green single actuator

## Actuator Inscription:

Remote local single actuator

## Maximum Voltage Rating In Volts:

28.0 dc

## Inclosure Type:

Fully enclosed

## Mounting Method:

Panel

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

#### **Special Features:**

Split display

## Precious Material And Location:

Contacts silver and terminals gold

## Unable To Decode:

Unable to decode and unable to decode

## Terminal Type And Quantity:

5 tab, solder lug and 3 turret

## Shelf Life:

N/a

# NSN 5930-01-201-1952

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

