NSN 5930-01-201-1956

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-201-1956

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Fungus resistant and moisture resistant and salt spray resistant and shock resistant and vibration resistant
Body Length:
0.750 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Width:
0.620 inches
Actuator Color:
Green single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Df big look single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc
Special Features:
Split display
Precious Material And Location:
Contacts silver and contacts gold
Unable To Decode:
Unable to decode and unable to decode
Terminal Type And Quantity:
5 tab, solder lug and 3 turret
Shelf Life:
N/a

NSN 5930-01-201-1956

Push Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0