NSN 5930-01-201-4441

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-201-4441
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight and watertight
Overall Length:
4.220 inches
Overall Height:
2.460 inches
Overall Width:
1.540 inches
Housing Height:
1.540 inches
Housing Length:
4.220 inches
Housing Width:
1.780 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Neutral terminal
Nonpile-up Contact Arrangement:
2 two circuit, one position momentary single switch unit
Switch Release Force:
4.5 inch-ounces
Switch Actuating Force:
48.0 inch-ounces
Actuator Movement:
5.0 pretrayel degrees, and 85.0 overtrayel degrees, and 2.0 differential degrees

5.0 pretravel degrees and 85.0 overtravel degrees and 2.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 0.600 amperes resistive ac

Special Features:

Side rotary head

Terminal Type And Quantity:

9 screw

NSN 5930-01-201-4441

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0