NSN 5930-01-201-4441

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-201-4441

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight and watertight

Overall Length:

4.220 inches

Overall Height:

2.460 inches

Overall Width:

1.540 inches

Housing Height:

1.540 inches

Housing Length:

4.220 inches

Housing Width:

1.780 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.160 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Neutral terminal

Nonpile-up Contact Arrangement:

2 two circuit, one position momentary single switch unit

Switch Release Force:

4.5 inch-ounces

Switch Actuating Force:

48.0 inch-ounces

Actuator Movement:

5.0 pretravel degrees and 85.0 overtravel degrees and 2.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 0.600 amperes resistive ac

Special Features:

Side rotary head

Terminal Type And Quantity:

9 screw

NSN 5930-01-201-4441

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

