

View Online at <https://aerobasegroup.com/nsn/5930-01-202-0186>

**Body Style:**

Bushing mounted

**Body Diameter:**

0.630 inches

**Bushing Length:**

0.875 inches

**Body Length:**

2.200 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.250 inches

**Actuator Free Position Height:**

Between 0.875 inches and 0.905 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Glcm

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc

**Special Features:**

Temp range m-55 degrees c to p-85 degc

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0