NSN 5930-01-202-0873

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-202-0873

View Online at https://aerobasegroup.com/nsn/5930-01-202-0873
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Bushing Length:
0.250 inches
Body Length:
0.500 inches
Body Width:
Between 0.440 inches and 0.460 inches
Body Height:
Between 0.460 inches and 0.480 inches
Actuator Style:
Round
Actuator Diameter:
0.200 inches
Actuator Height:
0.275 inches
Actuator Color:
Black single actuator
Black single actuator Maximum Voltage Rating In Volts:
-
Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts: 20.0 dc
Maximum Voltage Rating In Volts: 20.0 dc Inclosure Type:
Maximum Voltage Rating In Volts: 20.0 dc Inclosure Type: Fully enclosed
Maximum Voltage Rating In Volts: 20.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi):
Maximum Voltage Rating In Volts: 20.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 40
Maximum Voltage Rating In Volts: 20.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 40 Thread Size:
Maximum Voltage Rating In Volts: 20.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 40 Thread Size: 0.250 inches
Maximum Voltage Rating In Volts: 20.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 40 Thread Size: 0.250 inches Nonpile-up Contact Arrangement:
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unit
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:1.000 amperes resistive dc
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:1.000 amperes resistive dcPrecious Material And Location:
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:1.000 amperes resistive dcPrecious Material And Location:Contacts and terminal surfaces gold
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:1.000 amperes resistive dcPrecious Material And Location:Contacts and terminal surfaces goldThread Series Designator:
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:1.000 amperes resistive dcPrecious Material And Location:Contacts and terminal surfaces goldThread Series Designator:Uns
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedFully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:1.000 amperes resistive dcPrecious Material And Location:Contacts and terminal surfaces goldThread Series Designator:UnsTerminal Type And Quantity:
Maximum Voltage Rating In Volts:20.0 dcInclosure Type:Fully enclosedFully enclosedThready Qty Per Inch (tpi):40Thread Size:0.250 inchesNonpile-up Contact Arrangement:2 pole, double throw, both positions maintained single switch unitContact Load Current Rating At Maximum Rated Voltage:1.000 amperes resistive dcPrecious Material And Location:Contacts and terminal surfaces goldThread Series Designator:UnsTerminal Type And Quantity:6 tab, solder lug

NSN 5930-01-202-0873

Push Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

