

View Online at <https://aerobasegroup.com/nsn/5930-01-202-2459>

**Thread Class:**

2b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

5.188 inches

**Overall Height:**

4.983 inches

**Overall Width:**

2.812 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

216.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes inductive load fifth voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+10.00/+180.00 actuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level eighth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0