NSN 5930-01-202-2466

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-202-2466				
Body Style:				
Panel mount				
Hazardous Locations/environmental Protection:				
Shock proof				
Overall Length:				
1.000 inches				
Overall Height:				
3.430 inches				
Overall Width:				
1.000 inches				
Body Length:				
0.679 inches				
Body Width:				
0.750 inches				
Case Material:				
Metal				
Actuator Length:				
0.740 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.270 inches				
Actuator Width:				
0.740 inches				
Actuator Color:				
White single actuator				
Illuminated Actuator Color:				
Yellow single actuator				
Actuator Inscription:				
Blow open single actuator				
Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Features Provided:				
Actuator seal				
Nonpile-up Contact Arrangement:				
2 pole, double throw, one position momentary single switch unit				

O stand and O seed Both a Mile to a But IV Know

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-202-2466

Push Switch - Page 2 of 2



Precious	Material	And	Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0