NSN 5930-01-202-2470

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-202-2470					
Body Style:					
Panel mount					
Hazardous Locations/environmental Protection:					
Shock proof					
Overall Length:					
1.000 inches					
Overall Height:					
3.430 inches					
Overall Width:					
1.000 inches					
Body Length:					
0.679 inches					
Body Width:					
0.750 inches					
Case Material:					
Metal					
Actuator Length:					
0.740 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.270 inches					
Actuator Width:					
0.740 inches					
Actuator Color:					
White single actuator					
Illuminated Actuator Color:					
Yellow single actuator					
Actuator Inscription:					
Isol single actuator					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Features Provided:					
Actuator seal					
Nonpile-up Contact Arrangement:					
2 pole, double throw, one position momentary single switch unit					
Contact Load Current Rating At Maximum Rated Voltage:					

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-202-2470

Push Switch - Page 2 of 2



P	racions	Matarial	And	Location:
_	recious	wateriai	Allu	LOCALION.

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0