## NSN 5930-01-202-2508

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-202-2508

#### **Thread Class:**

2b single mounting facility

#### Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

#### **Overall Length:**

4.312 inches

#### **Overall Height:**

2.500 inches

**Overall Width:** 

3.000 inches

Individual Section Quantity:

#### 4

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Facility Circle Radius:**

1.156 inches single mounting facility

#### **Mounting Method:**

Bracket single mounting facility and threaded stud single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

120.0 dc at sea level

#### Mounting Facility Pattern:

Four position circular single mounting facility

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### **Terminal Type:**

Tab w/screw

#### **Contact Switching Action:**

Breaks before makes each section periphery

#### Switch Actuator Positioning Increment:

90.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

# NSN 5930-01-202-2508

Rotary Switch - Page 2 of 2

### **Thread Series Designator:**

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

