## NSN 5930-01-202-2508

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-202-2508

Thread C	lass:
----------	-------

2b single mounting facility

**Hazardous Locations/environmental Protection:** 

Shock resistant and vibration resistant

**Overall Length:** 

4.312 inches

**Overall Height:** 

2.500 inches

**Overall Width:** 

3.000 inches

**Individual Section Quantity:** 

4

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:** 

1.156 inches single mounting facility

**Mounting Method:** 

Bracket single mounting facility and threaded stud single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

120.0 dc at sea level

**Mounting Facility Pattern:** 

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

10.0 amperes resistive load dc at sea level

**Style Designator:** 

Tap, circuit selector

## NSN 5930-01-202-2508

Rotary Switch - Page 2 of 2



Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0