## NSN 5930-01-202-2515

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-202-2515
Hazardous Locations/environmental Protection:
Spraytight and watertight
Overall Length:
4.406 inches
Overall Height:
2.875 inches
Overall Width:
2.500 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.164 inches single mounting facility
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
1.062 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.062 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
440.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, threaded hole single actuator
Terminal Type:
Screw
Switch Actuator Ston Device Type:

Switch Actuator Stop Device Type:

Fixed stop single actuator

**Contact Load Current Rating:** 

15.0 amperes resistive load ac at sea level

## NSN 5930-01-202-2515

Rotary Switch - Page 2 of 2



Style	Des	siar	nato	r-
Otylo		, gi	iato	

In-line, cam actuated

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0