

View Online at <https://aerobasegroup.com/nsn/5930-01-202-3039>

Thread Class:

2a single threaded bushing

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Overall Length:

3.500 inches

Overall Height:

4.250 inches

Overall Width:

1.499 inches

Body Length:

2.062 inches

End Application:

Direction finder set an/bld-1

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -54.0 degrees celsius and 65.0 degrees celsius

Mounting Method:

Flange and threaded hole and threaded bushing

Thready Qty Per Inch (tpi):

18 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.625 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.20/+7.00 actuation point inches of water and +0.10/+4.00 deactuation point inches of water

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0