

View Online at <https://aerobasegroup.com/nsn/5930-01-202-3039>

**Thread Class:**

2a single threaded bushing

**Hazardous Locations/environmental Protection:**

Humidity resistant and vibration resistant

**Overall Length:**

3.500 inches

**Overall Height:**

4.250 inches

**Overall Width:**

1.499 inches

**Body Length:**

2.062 inches

**End Application:**

Direction finder set an/bld-1

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -54.0 degrees celsius and 65.0 degrees celsius

**Mounting Method:**

Flange and threaded hole and threaded bushing

**Thready Qty Per Inch (tpi):**

18 single threaded bushing

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.625 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+0.20/+7.00 actuation point inches of water and +0.10/+4.00 deactuation point inches of water

**Contact Adjustment Type:**

External actuation point hex nut and external deactuation point hex nut

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0