

View Online at <https://aerobasegroup.com/nsn/5930-01-202-4402>

Thread Class:

3a single pressure connection

Overall Length:

3.000 inches

Outside Diameter:

0.674 inches single connection

Overall Diameter:

0.890 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Plug-in terminal

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

7500.00 pounds per square inch gage

Terminal Type:

Connector, plug

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+2150.00/+2250.00 actuation point pounds per square inch gage and +1900.00/+2100.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0