# NSN 5930-01-202-5972

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-202-5972

## **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Shock proof

# **Overall Length:**

1.000 inches

### **Overall Height:**

3.430 inches

#### **Overall Width:**

1.000 inches

#### **Body Length:**

0.679 inches

#### **Body Width:**

0.750 inches

#### Case Material:

Metal

# Actuator Length:

0

# 0.740 inches

Actuator Style:

Rectangular

#### Actuator Height:

0.270 inches

### Actuator Width:

0.740 inches

#### Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

White single actuator

#### **Actuator Inscription:**

St0p single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

# **Features Provided:**

Actuator seal

# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

# NSN 5930-01-202-5972

Push Switch - Page 2 of 2



Precious Material And Location: Contact surfaces gold and contacts silver Unable To Decode: Unable to decode and unable to decode Terminal Type And Quantity: 1 socket, integrated wire termination Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A053a0