NSN 5930-01-202-6010

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-202-6010 **Thread Class:** 2b 1st mounting facility **Overall Length:** 7.970 inches **Overall Height: 3.688** inches **Overall Width:** 4.375 inches **Unthreaded Mounting Hole Diameter:** 0.312 inches 2nd mounting facility **Distance Between Mounting Facility Centers:** 3.812 inches 2nd mounting facility **Individual Section Quantity:** 16 **Longest Horizontal Distance Between Mounting Centers:** 2.281 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.281 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

20 1st mounting facility

Thread Size:

0.250 inches 1st mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

NSN 5930-01-202-6010

Rotary Switch - Page 2 of 2



Ī	hread	Series	Designator	r:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0