

View Online at <https://aerobasegroup.com/nsn/5930-01-202-6234>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Oiltight and submersible and watertight and driptight

**Case Material:**

Metal

**Housing Height:**

1.875 inches

**Housing Length:**

3.125 inches

**Housing Width:**

1.562 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.469 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.156 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 240.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.190 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

72.0 inch-ounces

**Actuator Movement:**

10.0 pretravel degrees and 80.0 overtravel degrees and 4.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

0.110 amperes resistive dc and 0.110 amperes inductive dc and 1.200 amperes inductive ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0