

View Online at <https://aerobasegroup.com/nsn/5930-01-202-6234>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight and submersible and watertight and driptight

Case Material:

Metal

Housing Height:

1.875 inches

Housing Length:

3.125 inches

Housing Width:

1.562 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.469 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.190 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

72.0 inch-ounces

Actuator Movement:

10.0 pretravel degrees and 80.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

0.110 amperes resistive dc and 0.110 amperes inductive dc and 1.200 amperes inductive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0