

View Online at <https://aerobasegroup.com/nsn/5930-01-202-8432>

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

0.623 inches

**Body Length:**

0.830 inches

**Actuator Style:**

Round, stepped

**Actuator Diameter:**

0.700 inches

**Actuator Height:**

0.410 inches

**Actuator Position-action Relationship:**

Center position maintained and left position momentary and right position momentary and up position maintained

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Recessed white filled arrows single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Mounting Surface To Terminal End Distance:**

1.000 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 four throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes inductive dc

**Test Data Document:**

81349-mil-s-9419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 tab, solder lug and 1 turret

**Specification Data:**

81349-mil-s-9419/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0