

View Online at <https://aerobasegroup.com/nsn/5930-01-203-3627>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

1.170 inches

Overall Height:

2.710 inches

Overall Width:

1.100 inches

Bushing Length:

0.470 inches

Body Width:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

1.050 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

1.100 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

8 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Precious Material And Location:

Contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

24 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0