

View Online at <https://aerobasegroup.com/nsn/5930-01-203-5700>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

0.660 inches

Body Width:

0.650 inches

Actuator Style:

Rectangular

Actuator Height:

1.240 inches

Actuator Width:

0.750 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position locked in and out and down position no locking action and center position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 5.0 dc

Mounting Surface To Terminal End Distance:

1.280 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Rfi shielding

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 milliamperes resistive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0