

View Online at <https://aerobasegroup.com/nsn/5930-01-203-5700>

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

0.660 inches

**Body Width:**

0.650 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

1.240 inches

**Actuator Width:**

0.750 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and out and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

115.0 ac and 5.0 dc

**Mounting Surface To Terminal End Distance:**

1.280 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Rfi shielding

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary, two positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 milliamperes resistive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0