

View Online at <https://aerobasegroup.com/nsn/5930-01-203-5708>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.624 inches

First Flat Length:

0.250 inches 1st actuator

Flat Height:

0.216 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.437 inches 2nd actuator

Overall Diameter:

1.265 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device 1st actuator

Switch Actuator Indexing Position Quantity:

3 all actuators

Shaft Type:

Round, flatted, threaded hole 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

1.3 amperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0