NSN 5930-01-203-6078

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-203-6078



Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.096 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Clear single actuator

Actuator Inscription:

1 khz single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

2.996 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

NSN 5930-01-203-6078

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Switching action is maintained depressed alternate

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0