NSN 5930-01-204-1409

Push Switch - Page 1 of 2

Body Style:Panel mount



View Online at https://aerobasegroup.com/nsn/5930-01-204-1409

Hazardous Locations/environmental Protection:
Moisture proof and shock resistant
Overall Length:
1.200 inches
Overall Height:
3.525 inches
Overall Width:
1.200 inches
Body Length:
1.200 inches
Body Width:
1.200 inches
Body Height:
3.150 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Actuator Color:
Green single actuator and yellow single actuator
Illuminated Actuator Color:
Green single actuator and yellow single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Radar set an/sps-6 (v) 1
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

4 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-01-204-1409

Push Switch - Page 2 of 2



Special Feature	es:
-----------------	-----

Horizontal split lens

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 socket, integrated wire termination

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0