

View Online at <https://aerobasegroup.com/nsn/5930-01-204-1412>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Moisture proof and shock resistant

**Overall Length:**

2.960 inches

**Overall Height:**

0.740 inches

**Overall Width:**

0.740 inches

**Body Width:**

0.740 inches

**Body Height:**

0.740 inches

**Actuator Length:**

0.740 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.300 inches

**Actuator Width:**

0.740 inches

**Actuator Color:**

Green single actuator and white single actuator

**Illuminated Actuator Color:**

Green single actuator and white single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Radar set an/sps-6 (v) 1

**Mounting Surface To Terminal End Distance:**

2.660 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

**Special Features:**

Horizontal split lens

**Precious Material And Location:**

Terminal surfaces gold

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

12 pin

**Specification Data:**

81349-mil-s-22885/80 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0