NSN 5930-01-204-1414

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-204-1414

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Moisture proof and shock resistant
Overall Length:
0.740 inches
Overall Height:
2.960 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Actuator Color:
Green single actuator and yellow single actuator
Illuminated Actuator Color:
Green single actuator and yellow single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Radar set an/sps-6 (v) 1
Mounting Surface To Terminal End Distance:
2.660 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

NSN 5930-01-204-1414

Push Switch - Page 2 of 2

Special Features:

Fiig: A053a0



Horizontal split lens
Precious Material And Location:
Terminal surfaces gold
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
11 pin
Specification Data:
81349-mil-s-22885/80 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No.