

View Online at <https://aerobasegroup.com/nsn/5930-01-204-4845>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Moisture proof and shock resistant

Overall Length:

3.525 inches

Overall Height:

1.200 inches

Overall Width:

1.200 inches

Body Length:

1.200 inches

Body Width:

0.975 inches

Body Height:

0.975 inches

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Height:

0.300 inches

Actuator Width:

0.740 inches

Actuator Color:

White single actuator and yellow single actuator

Illuminated Actuator Color:

White single actuator and yellow single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Radar set an/sps-6 (v) 1

Mounting Surface To Terminal End Distance:

3.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Special Features:

Horizontal split lens

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 socket, integrated wire termination

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0