NSN 5930-01-204-6138

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Moisture proof and shock resistant

Body Style: Panel mount

Overall Length: 1.200 inches Overall Height: 3.525 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5930-01-204-6138

| 1.200 inches |
|---|
| Body Length: |
| 1.200 inches |
| Body Width: |
| 1.200 inches |
| Body Height: |
| 3.150 inches |
| Actuator Length: |
| 0.740 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.300 inches |
| Actuator Width: |
| 0.740 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| Radar set an/sps-6 (v) 1 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Rfi shielding |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac |
| |
| |
| |

NSN 5930-01-204-6138

Push Switch - Page 2 of 2



Terminal surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 socket, integrated wire termination

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0