

View Online at <https://aerobasegroup.com/nsn/5930-01-204-7326>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Flame resistant

Overall Length:

1.375 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Body Diameter:

0.562 inches

Bushing Length:

0.312 inches

Body Length:

0.782 inches

Case Material:

Metal

Actuator Diameter:

0.375 inches

Actuator Height:

0.250 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

0.03 ac and 0.03 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 milliamperes resistive dc and 10.000 milliamperes resistive ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Specification Data:

96906-ms25089 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0

Mil-std (military Standard):

Mil-s-8805 spec.