

View Online at <https://aerobasegroup.com/nsn/5930-01-205-1832>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Watertight and shock proof

Overall Length:

3.520 inches

Overall Height:

1.740 inches

Overall Width:

2.120 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 all actuators

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Contact Load Current Rating:

7.5 amperes inductive load highest ac voltage rating at sea level

Special Features:

Mtg plate legend reads local loc/rem

Style Designator:

Rectangular panel mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0