NSN 5930-01-205-2632

Thermostatic Switch - Page 1 of 2

Unthreaded Mounting Hole Diameter:

Overall Length:
5.188 inches
Overall Height:
5.406 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches

0.281 inches



View Online at https://aerobasegroup.com/nsn/5930-01-205-2632

Distance Between Mounting Facility Centers:
5.250 inches
Capillary Tube Length:
240.0 inches
Bulb Length:
1.125 inches
Bulb Diameter:
6.000 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Two position in-line Nonpile-up Contact Arrangement:
·
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type:
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating:
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating: 0.5 amperes resistive load fourth voltage
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating: 0.5 amperes resistive load fourth voltage Contact Adjustability:
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating: 0.5 amperes resistive load fourth voltage Contact Adjustability: Actuation point adjustable
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating: 0.5 amperes resistive load fourth voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range:
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating: 0.5 amperes resistive load fourth voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: -20.00/+100.00 actuation point degrees fahrenheit
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating: 0.5 amperes resistive load fourth voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: -20.00/+100.00 actuation point degrees fahrenheit Contact Adjustment Type:
Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Screw Contact Load Current Rating: 0.5 amperes resistive load fourth voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: -20.00/+100.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw

NSN 5930-01-205-2632

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0